

G AND H SERIES — ECONOMICAL GRANULATORS

APPLICATIONS

The compact granulators of the G and H series are primarily designed for use in injection and blow moulding applications to recycle voluminous parts such as bottles, canisters and crates, as well as blow moulding flush and injection sprues. The low height makes them ideally suitable for the manual feeding of such parts. The low noise level and small footprint makes them the perfect fit for inline recycling operations.

GENERAL DESCRIPTION

The economical granulators of the G and H series are available in two rotor diameters, 250 and 400 mm with widths ranging from 300 to 1000 mm.

The G series features an open F rotor while the H series relies on a heavier S rotor. The curved and highly tangential backwall of the cutting chamber ensures an aggressive ingestion while also avoiding blockages. The rigid design makes them dependable units and includes advanced standard features such as replaceable wear plates. The rotor and stator knives are adjusted outside of the machine to reduce downtime for maintenance.

ADVANTAGES

- » Compact design, small footprint
- » All knives are adjusted outside of the machine in a jig to reduce downtime for maintenance
- » Aggressive infeed due to curved backwall of the cutting chamber
- » Large screen area for high throughput rates
- » Modern V-cut technology creates a high-quality regrind while reducing energy consumption and noise



G and H Series		G 30	G 45	G 60	H 60	H 100
Rotor diameter	(mm)	250	250	250	400	400
Rotor width	(mm)	300	450	600	600	1000
Drive capacity	(HP)	10	15	20	30	40
Rotor knives	(pcs)	3 x 1	3 x 1	3 x 2	3(5) x 2	3(5) x 2
Stator knives	(rows)	2	2	2	2	2
Feed opening	(mm)	340 x 300	340 x 450	340 x 600	490 x 590	490 x 990
Dimensions						
Length A	(mm)	1207	1207	1348	1348	1348
Length B	(mm)	860	860	1000	1120	1120
Width C	(mm)	870	1020	1165	1177	1577
Width D	(mm)	440	684	834	816	1216
Height E	(mm)	1712	1712	1712	1914	1914

Crushmaster Ltd.

12/F Ruttonjee House · 11 Duddell Street, St. Central · Hongkong · China · Phone: +852 28109783 Sales Office and Showroom

V. Warehouse (B.2) \cdot 67/28 Moo 8 \cdot Tambon Tabma \cdot Amphur Muang \cdot Rayong 21000 \cdot Thailand Phone: +66 3 8026 900-1 \cdot Fax: +66 3 8026 121 \cdot sales@crushmaster.com

